
THORN

Cesar

Versatile and contemporary architectural floodlight with extensive wall applications







applications

The Cesar range offers architects and consultants an approach to exterior lighting that combines creative possibilities with practical benefits

Wide range of applications

The Cesar range is highly flexible, IP65 protected, and designed in aluminium for durability. It offers excellent photometric performance and, with its extensive range of light sources, lenses and reflectors including adjustable versions, it offers designers and architects an almost infinite choice of effects combined with valuable benefits. For greater versatility the dual light emission in sizes 3 and 4 can operate independently. Typical applications include building façades, pedestrian areas such as paths and pavements, porches, columns and balconies.






Version available using LED technology

LEDs are compact, inherently rugged and highly energy efficient, with long operating lifetimes. They produce little heat and no UV radiation and operate at very low power, making them ideal for public environments and use close to sensitive displays such as works of art. LED technology is also instant, dimmable and available in a range of colours as well as white light. As well as energy savings, LEDs further benefit the environment by requiring fewer raw materials, and no mercury, during manufacture.















Red colour filter (attachment)

Cesar's simple, cylindrical style, available in four sizes, offers a choice of adjustable light sources and superior highlighting

wide range of versions

All models are available with either downward or up/down illumination and a wide range of light sources

- By day, Cesar adds to the style and ambience of its surroundings. It has a modern, cylindrical design that is particularly well suited to the high tech theme of today's architectural developments
- By night, Cesar comes into its own, adding safety, security and a new aesthetic dimension to its context. It can emphasise with drama or subtlety, the features of fine architecture
- Strong, die-cast aluminium construction combines understated elegance with high durability

- Stainless steel screws promote additional resistance and easy maintenance
- IP65 protection
- Other RAL colours available on request
- Range of lamp types, lenses and wattages optimise light output and save energy
- Delivered with integral gear
- Safe and simple installation using a single tool
- Automatic connection reduces installation time and cost
- Double lamp versions available with independent electric circuits provide energy savings and help to control obtrusive light


lighting effects

- Adjustable lamp positioning (except for TC-TEL models) enhances versatility
- Intensive and semi-intensive reflectors combine excellent photometric performance with choice of beam angles, for creative effects (intensive reflectors and ellipsoidal lens available as a custom request)

With one luminaire you can obtain both up and down light distributions. During busy periods you would use the dual light emission but later at night you can switch to down light only, preventing obtrusive light.


















colour filters

- Colour effects can be created using the LED version of Size 1. Colours available include red, green, blue, yellow and white (6000K)
- All other sizes offer colour filter attachments in red, green, blue and yellow
- Frosted glass attachment available for diffused light





Ordering guide Dimensions Data



Lamps

→ 3W LEDS (size 1 only)

□ 35W, QR-CBC (HRG)

Halogen. Cap: GU5.3

□ 75W, QPAR30 (HAPAR)

Halogen. Cap: E27

□ 18-42W, TC-TEL (FSM)

compact fluorescent.

Cap: GX24q2/3/4

□ 35W, HIT-TC-CE (MT)

metal halide. Cap: G8.5

□ 70-150W, HIT (MT)

metal halide. Cap: G12

□ 70W, HST (ST) high

pressure sodium. Cap: E27

Materials/Finish

Body and frame: die-cast aluminium EN AB4700 and extruded ENAW 6060 housing (copper free) with high corrosion resistance and powdered painted close to RAL 9007 with corrosion resistance.

Reflector: pure aluminium Front glass: toughened glass, thickness 6mm - size 1, 8mm - size 2 and 3, 12mm - size 4.

Retaining screws: stainless steel INOX Gasket: silicone

Installation/Mounting

Suitable for exterior wall mounting. Fast connectors for electrical connection, cable diameters, size 1 min: 8mm, max: 12mm, size 2, 3 and 4 min: 6mm, max: 12mm.

Standards

Designed and manufactured to comply with EN 60598

discrete Class I electrical
IK 08 ◆ ▲ ▲ IP65 C€

Specification

To specify state:
Contemporary wall mounted floodlight for 3W LED/35W QR-CBC/75W QPAR30 Halogen 18-42W TC-TEL/35W HIT-TC-CE/70-150W HIT and 70W HST, in 4 sizes, IP65 protected, gear integrated, optional colour filters, frosted glass or louvre available as accessories.

As Thorn Cesar

Ordering Guide Lamps to be ordered separately (except LED)

Ordering Guide Lamps to be ordered separately (except LED)					
Description		Ilcos Code	Socket	Wt (kg)	Sap Code
Cesar size 1 LED versions	- Downlight only				
CESAR 1 1X3W 3LED WHI	.	NA	NA	1.7	96231435
CESAR 1 1X3W 3LED BLU		NA	NA	1.7	96231436
CESAR 1 1X3W 3LED GRN		NA	NA	1.7	96231437
CESAR 1 1X3W 3LED RED		NA	NA	1.7	96231438
CESAR 1 1X3W 3LED YEL		NA	NA	1.7	96231439
Cesar size 1 LED versions - Up/Downlight					
CESAR 1 2X3W 3LED WHI		NA	NA	1.9	96231452
CESAR 1 2X3W 3LED BLU		NA	NA	1.9	96231453
CESAR 1 2X3W 3LED GRN		NA	NA	1.9	96231454
CESAR 1 2X3W 3LED RED		NA	NA	1.9	96231455
CESAR 1 2X3W 3LED YEL		NA	NA	1.9	96231456
Cesar size 1 - Downlight only					
CESAR 1 1x35W 12V QR-CBC	C51/GU5,3	HRG	GU5.3	1.8	96231434
Cesar size 1 - Up/Down					
CESAR 1 2X35W 12V QR-CB0	C51/GU5,3	HRG	GU5.3	2.0	96231451
Cesar size 2 - Downligh	t only				
CESAR 2 1X75W QPAR30/E2		HAPAR	E27	2.1	96231462
CESAR 2 1X18W TC-TEL/GX2	4-q2	FSM	GX24-q2	3.2	96231463
CESAR 2 1X35W HIT-TC-CE/G	8,5	MT	G8.5	4.3	96231464
Cesar size 2 - Up/Down	light				
CESAR 2 2X75W QPAR30/E2	7	HAPAR	E27	3.8	96231465
CESAR 2 2X18W TC-TEL /GX2	24-q2	FSM	GX24-q2	4.4	96231466
CESAR 2 2X35W HIT-TC-CE/G		MT	G8.5	6.9	96231467
Cesar size 3 - Downlight only					
CESAR 3 1X26/42W TC-TEL/0		FSM	GX24q-3/4	7.3	96231474
CESAR 3 1X70W HIT/G12		MT	G12	8.7	96231475
CESAR 3 1X70W HST/E27		STH	E27	8.7	96231476
Cesar size 3 - Up/Down					
CESAR 3 2X26/42W TC-TEL/0		FSM	GX24q-3/4	8.6	96231477
CESAR 3 2X70W HIT/G12	1.7	MT	G12	11.7	96231478
CESAR 3 2X70W HST/E27		STH	E27	12.6	96231479
Cesar size 4 - Downlight only					
CESAR 4 1X150W HIT/G12	Olly	MT	G12	14.3	96231490
C	PL.				
Cesar size 4 - Up/Down CESAR 4 2X150W HIT/G12	lignt	MT	G12	19.9	96231493
CL3AK 4 2X130VV 1111/G12		74(1	012	17.7	70231473
Accessories					
CESAR 1 FILTER BLU	SIZE 1 BLUE FILTER			0.1	96231457
CESAR 1 FILTER GRN	SIZE 1 GREEN FILTER			0.1	96231458
CESAR 1 FILTER RED	SIZE 1 RED FILTER			0.1	96231459
CESAR 1 FILTER YEL	SIZE 1 YELLOW FILTER			0.1	96231460
CESAR 1 FILTER FR	SIZE 1 FROSTED GLASS			0.1	96231461
CESAR 2 FILTER BLU	SIZE 2 BLUE FILTER			0.2	96231468
CESAR 2 FILTER GRN	SIZE 2 GREEN FIL			0.2	96231469
CESAR 2 FILTER RED	SIZE 2 RED FILTER			0.2	96231470
CESAR 2 FILTER YEL	SIZE 2 YELLOW F			0.2	96231471
CESAR 2 FILTER FR	2			0.2	96231472
CESAR 3 FILTER BLU	SIZE 3 BLUE FILTER			0.2	96231480
CESAR 3 FILTER GRN	SIZE 3 GREEN FILTER SIZE 3 RED FILTER			0.2	96231481
CESAR 3 FILTER RED CESAR 3 FILTER YEL	SIZE 3 YELLOW F			0.2	96231482 96231483
CESAR 3 FILTER FR	SIZE 3 YELLOW F			0.2	96231483
CESAR 4 FILTER BLU				0.2	96231494
CESAR 4 FILTER GRN SIZE 4 GREEN FILTER				0.3	96231494
CESAR 4 FILTER RED SIZE 4 RED FILTER				0.3	96231496
CESAR 4 FILTER YEL	SIZE 4 YELLOW F			0.3	96231497
CESAR 4 FILTER FR SIZE 4 FROSTED O				0.3	96231498
CESAR 3/4 LV ANTI GLARE 🔘 ANTI GLARE LOUVRE FOR SIZE 3/4				0.1	96231485



Lighting people and places

Thorn Lighting Limited

Silver Screens, Elstree Way, Borehamwood, Hertfordshire, WD6 1FE

UK Sales desk -**Orders/Stock Enquiries** 08701 610 610 Tel: 08701 610 611 Fax: **Project Enquiries:**

08701 610 710 08701 610 711 Fax:

Ireland

320 Harold's Cross Road, Dublin 6W (353) 1 4922 877 Tel: (353) 1 4922 724 Fax: enq.dublin@thornlight.com E-mail:

Outdoor Lighting

Silver Screens, Elstree Way, Borehamwood, Hertfordshire, WD6 1FE

020 8732 9829 020 8732 9825

enquiries.outdoor@thornlight.com E-mail:

Airfield Lighting

Silver Screens, Elstree Way, Borehamwood,

Hertfordshire, WD6 1FE Tel: 020 8732 9804 020 8732 9803 Fax: airfield@thornlight.com Website: www.thornairfield.com

Spare Parts

0191 301 3131 0191 301 3038 E-mail: spares@thornlight.com

Technical Support

0870 600 8111 0191 301 3907 F-mailtechnical@thornlight.com

Brochureline Answering Service

Brochures on specific products/ranges Tel: 020 8732 9898

020 8732 9899 Fax: brochures@thornlight.com E-mail:

International Sales

Silver Screens, Elstree Way, Borehamwood,

Hertfordshire, WD6 1FE 020 8732 9802 020 8732 9803

E-mail: international.sales@thornlight.com

Thorn Lighting Ltd Dubai

Al Shoala Building, Office 301,

Block E, PO Box 1200, Deira, Dubai, UAE

Tel: (971) 4 2940181 (971) 4 2948838 Fax: tlluae@emirates.net.ae

Thorn Gulf LLC

Al Shoala Building, Office 301/2, Block E, PO Box 1200, Deira, Dubai, UAE

Tel: (971) 4 2948938 Fax: (971) 4 2948838 E-mail: thorng@emirates.net.ae

Other Offices in:

Australia, Austria, China, Czech Republic, Denmark, Estonia, France, Hong Kong, Italy, Latvia, Lithuania, New Zealand, Norway, Poland, Russia, Singapore, Sweden and UAE

www.thornlighting.co.uk

Thorn Lighting is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. The right is reserved to change specifications without prior notification or public announcement. All goods supplied by the company are supplied subject to the company's General Conditions of Sale, a copy of which is available on request. All measurements are in millimetres and weights in kilograms unless otherwise stated.

