96267279 <SATIN2 MRE L1250 48L33 A/S 830 IO

IP68	IK10		CE	T_a25

A discreet floor recessed linear floodlight for façade illumination applications. 48 LEDs driven at 330mA with asymmetrical distribution. Electronic, fixed output control gear. Body: extruded aluminium (EN AW-6060 T6) painted textured silver grey. Sides: die-cast aluminium painted textured silver grey. Enclosure: tempered glass 10mm thick. Class II electrical (this product is not earthed), IP68, IK10. Pre-wired with 1m of 2x1mm² H05RNF cable at both ends. Complete with 3000K LED

Dimensions: 1254 x 96 x 112 mm
Luminaire input power: 46 W
Weight: 6 kg

TLG_STN2_F_PDBMRE.jpg



TLG_SATL_M_LD1_03.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting