Arena Symphony

96645144 ARENA LED6500-840 HFIX E3 TW WL6 EFL

IP20	IK03		CE			650°C	Ta 0 +25	

Arena Symphony

A suspended architectural raft, incorporating a direct/indirect LED luminaire. Electronic, DALI dimmable control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP20. Raft and luminaire frame: aluminium. Optic: flat acrylic. Supplied with a 6 pole Wieland plug on 3.4m of 6 core cable and a panel mounted 6 pole Wieland socket for through wiring. Supplied with suspension wires. Complete with 4000K LED.

Dimensions: 2200 x 850 x 100 mm
Luminaire input power: 55.5 W
Luminaire luminous flux: 6300 lm
Luminaire efficacy: 114 lm/W
Weight: 24.6 kg

TLG_ARNS_F_EFL.jpg



TLG_ARNS_M_LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Arena Symphony

96645144 ARENA LED6500-840 HFIX E3 TW WL6 EFL

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting