THORN

96100186 <PETRELUX P7 1x36w T26 HF

IP66		CE			850°C	7Nm	Ta 40 55

ATEX Category 2 Certificated flameproof EExd linear fluorescent luminaire

Zone 1 (ATEX Cat 2) fluorescent luminaire for 1 x 36W Light Source: 1 x T26 / 36W lamp. Integral high frequency electronic ballast. Body and covers manufactured from die cast aluminium alloy with Petrelux Green 2 pack epoxy paint finish. Overtube clear polycarbonate. IP66 to IEC 529. Certification code EEx de 11B for 36w, 58w and 70w T26 versions. EEx de 11C for 18w T26, 36w and 55w TC-L versions. Temperature class T6 (70w T26 versions T5)

Dimensions: 1362 x 140 x 158 mm
Luminaire input power: 36 W
Weight: 7 kg

TLG_PTLX_F_7EM.jpg

All values marked with an * are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

96100186 <PETRELUX P7 1x36w T26 HF

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting