Discontinued

96627686 <OMEGA PRO 4100 HFIX Q597 MRM LED830

Discontinued

A ceiling recessed edge lit LED luminaire with a slim 19mm profile. For installation from below into concealed metal ceilings. Electronic, DALI / DSI digital dimmable control gear. Class II electrical (this product is not earthed), IP40 from below, IP40_IP20 from above, IK03. Body: steel sheet white (RAL9016). Diffuser: UV-stabilised, Glare ProTech prismatic optic. Electrical connection via push wire terminal blocks, loop in/loop out possible. Complete with 3000K LED

Dimensions: 597 x 597 x 12 mm
Luminaire input power: 41 W
Luminaire luminous flux: 3950 lm
Luminaire efficacy: 96 lm/W
Weight: 6 kg



TLG_OMGP_F_597CGRID.jpg



TLG_OMPL_M_LDSQ.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting