96643233 <NOVALINE LED1800-840 HF E3TX WH

IP40 | IK02 | 850°C | Ta 0 +25

A round bulkhead LED luminaire. Electronic, fixed output control gear with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body and bezel: finish, spun aluminium. Diffuser: opal polycarbonate. Class I electrical, IP40. Complete with 4000K LED.

Dimensions: Ø455 x 105 mm
Luminaire input power: 15.5 W
Luminaire luminous flux: 1800 lm
Luminaire efficacy: 116 lm/W
Weight: 2.34 kg

TLG_NOVN_F_1000LEDWALLPDB.jpg



TLG_NOVN_M_LED2.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

THORN

96643233 <NOVALINE LED1800-840 HF E3TX WH

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting