ImpactForce

A high performance impact resistant, IP65 proof range

- Unique shape and flush toggle design promotes easy cleaning
- For quick and easy maintenance, gear tray simply hangs from internal clips
- Vandal resistant



180° 150° 150° 120° 120° 287 720 32 347 900 120 260 90° 180 90 124 156 216 60° 60° 1294 28/54W 1594 35/49/80W 30 30 0° 1 x T16 (T5) cd/klm 96234460

Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.

Material/Finish

Canopy: glass-fibre reinforced polyester Diffuser: polycarbonate with linear prisms Gasket: expanded polyurethane Toggles: stainless steel Gear tray: steel, white enamelled finish

Installation/Mounting

Cable entry positions at the back and each end of the fitting. Supplied with IP65 grommet. Stainless steel quick-fix brackets supplied with each luminaire. Stainless steel toggles are captive in the canopy to prevent loss during maintenance, and steel gear tray is retained by spring latches. BESA box and conduit mounting, chain suspension and catenary suspension kits, plus through wire kits are all available as accessories. LED version: through wiring end to end is not possible but looping in and out at one end is acceptable. LSOH cabling as standard. Suitable for all indoor plus external 'under cover only' applications

Specification

To specify state:

High performance, IP65, dust and moisture proof impact resistant luminaire with GRP canopy, polycarbonate diffuser and stainless steel toggles, digital dimming and emergency options. As Thorn ImpactForce II.