




Oxane

A stylish road lantern at the forefront of LED technology designed to deliver excellent lighting and through-life performance

- High efficiency road lighting lantern available in several ratings from 15W (1300 lm) to 85W (7000 lm) covering lighting classes up to ME3
- Highly efficient road lantern available in two light distributions and different ratings to offer best combination to any road type
- Modularity allows through-life performance improvements by simply changing the optical engine and driver as more efficient systems emerge
- Minimal and easy maintenance with a long 90,000-hour lifetime, self-cleaning shape, wide and tool-free canopy opening, and fully removable gear



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.



96265601

Material/Finish

Body & spigot: die-cast aluminium, powder coated texturised light grey (close to RAL9006)
Enclosures: toughened glass, self cleaning treatment on request
Screws: stainless steel

Installation/Mounting

Rotating spigot secured by 2 screws with safety bolts. Post-top mounting: Ø60/76 mm x 80 mm long spigot. Tilted to 5°. Lateral mounting: CL1 - Ø34/42/49/60 mm x 120mm / CL2 - Ø49/60 mm x 120 mm long spigot. Tilted to 0°. Cable gland for Ø8-13 mm cable. Delivered ready to install in 1 box.

Specification

To specify state:

Easy to install and maintain LED luminaire designed to offer effective and reliable lighting performances with combined thermal and optical system. Suitable for main road lighting applications.

As Thorn Oxane.