

## Avenue F2


# Post top lantern with a distinctive design and lighting signature


- IDA Dark Sky Approved
- \*IDA fixture seal of approval relates to <= 3000 K only and clear enclosures. Luminaires must be mounted as photometered.
- With conical bowl and prismatic crown for reduced glare and distinctive appearance
- With flat enclosure for minimum upward lighting, preserving dark skies
- Connectivity with Zhaga socket
- Choice of dimming options and controls to reduce energy consumption and preserve dark skies
- OTHER OPTIONS ARE AVAILABLE (colour temperature, controls, colour...). See myProduct for configuration options



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96260128

### Material/Finish

Base and arms: die cast aluminium (AS9U3, LM24 equivalent, EN AC-46000, standard corrosion class C3).

Canopy: spun aluminium

Finish: texturised anthracite (close to RAL7043), Choice of RAL colors via Myproduct

Diffuser: clear UV stabilised PC Screw fixings: stainless steel

## Installation/Mounting

Suitable for mounting on top Ø76mm or Ø60mm, spigot internal length: 100mm. Recommended height: 3/4m. Equipped with cable gland or pre-wired with HO5VVF cable. Spare drivers and LED modules available. Delivered ready to install, complete with factory fitted integral gear tray, all supplied in a single carton.

### **Specification**

To specify state:

Post top decorative lantern with 4 brackets, 2 different bowl enclosures: one conical with prismatic crown for distinctive lighting signature, the second with a flat enclosure to minimize lighting pollution. A choice of optics, controls and Zhaga connectivity addressing urban applications like parks, plazas, streets.

As Thorn Avenue F2.



# **Avenue F2**

## Ordering Guide Supplied complete with LEDs

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
Avenue F2 with conical bowl				
AVF 18L70-740 WST CL BS 3550 CL1 CON ->	LED		9,2	96260033
AVF 18L70-740 WST CL PM CL1 CON T76 ANT	LED		9,3	96260034
AVF 18L70-740 RS CL BS 3550 CL1 CON ->	LED		9,1	96260021
AVF 18L70-740 RS CL BS 3550 CL1 CON ->	LED		9	96260059
AVF 18L70-740 WST CL BS 3550 CL1 CON ->	LED		9,3	96260096
AVF 18L50-740 RS CL BS 3550 CL1 CON ->	LED		9	96260127
AVF 18L35-740 RS CL BS 3550 CL1 CON ->	LED		9	96260128
AVF 18L35-740 WST CL BS 3550 CL1 CON ->	LED		9,3	96260231
AVF 18L50-740 WST CL BS 3550 CL1 CON ->	LED		9,3	96260232
AVF 18L70-730 WST CL BS 3550 CL1 CON ->	LED		9,3	96265454
AVF 18L50-730 RS CL BS 3550 CL1 CON ->	LED		9	96265461
AVF 18L35-730 RS CL BS 3550 CL1 CON ->	LED		9	96265462
AVF 18L35-730 WST CL BS 3550 CL1 CON ->	LED		9,3	96265463
AVF 18L50-730 WST CL BS 3550 CL1 CON ->	LED		9,3	96265464
AVF 18L35-740 RS CL BS 3550 CL1 CON ->	LED		9	96265465
AVF 18L70-730 RS CL BS 3550 CL1 CON ->	LED		9,1	96265443
AVF 18L50-730 RS CL BS 3550 CL1 CON ->	LED		9	96265466
AVF 18L70-730 WST CL BS 3550 CL1 CON ->	LED		9,2	96265445
AVF 18L35-730 RS CL CL1 CON T60 ANT	LED		9	96672111
AVF 18L50-730 RS CL CL1 CON T60 ANT	LED		9	96672112
AVF 18L70-730 RS CL CL1 CON T60 ANT	LED		9	96672113