

Leopard


Series of vandal resistant luminaires for wall or ceiling mounting, in black or white with opal or prismatic diffusers


- Sealed to IP65 for exterior applications when supplied gasket fitted
- Energy saving sensor options, luminaire is activated when movement has been detected, then will switch off
- · Integral emergency version as standard
- Wiith sensor and emergency lighting options



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96617046

Material/Finish

Bodies: polycarbonate, black or white

Diffusers: polycarbonate opal and clear honeycomb prismatic

Geartray: Pre-coated steel

Installation/Mounting

Suitable for surface mounting with rear BESA provision, side entry (25mm conduit) for through wiring with entry into 3 way terminal block suitable to accept 2 x 2.5mm. Vandal resistant screw kit available as an accessory. Sensor options have adjustments for sensitivity, daylight and activated period.

All internal components are fixed to a white pre-coated gear tray which has a unique (tool free) click fit into base. Switch start and High Frequency ballast, 240V 50/60 Hz

Specification

To specify state:

Polycarbonate bulkhead with black/white base, tool-less gear tray fixation.

With unique honeycomb prismatic or opal diffuser.

As Thorn Leopard.

EN60598, TC-DD, TC-DDEL, Beam_Surface_1, IP65, IK10, Beam_Wall_6, Beam_eControl_A, SC1, Beam_Emergency, CE, RCM, TC-S, 850, Ta=25, LED