


Cetus LED

THORN

96242099 CETUS LED 1000 HF E3 840



Cetus LED

A value performance, low height, ceiling recessed LED downlight. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Body and reflector: aluminium, powder coated white (RAL 9016). Diffuser: polycarbonate. Class I electrical, IP44, IK09. Spring clips suitable for ceiling thicknesses from 1 to 35mm. Cut-out Ø190mm. Complete with 4000K LED.


Dimensions: Ø215 x 88 mm

Total power: 9.4 W

Weight: 1.75 kg



TLG_CTUL_F_LED.jpg



TLG_CETU_M_E3.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Colour temperature is subject to a tolerance of up to ± 150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C .

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting