

Primata LED

THORN

96627520 PRIM L3 LED19000-840 NB HFIX SET



Primata LED

3000 mm length of trunking, for direct ceiling fixing or suspended mounting on wire or chains, with 19,000 lm LED luminaire with narrow distribution.. Roll-formed steel sheet in white Polyester lacquered finish. Class I electrical, IP20. Standard module, with mechanical connector. Supplied with plug-in, 7-pole through wiring. Complete with side panels. Complete with 4000K LED.

Dimensions: 3000 x 68 x 93 mm

Total power: 127 W


Luminaire luminous flux: 19000 lm

Luminaire efficacy: 150 lm/W

Weight: 8.3 kg



TLG_PMM5_F_LEDpdb.jpg



TLG_PMML_M_LED_bestueckt.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Colour temperature is subject to a tolerance of up to ± 150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C .

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting