

Omega Pro 2

92916282 OP2 3800-840 HX HF E3D Q600

| | | | | | | | | | | | |
|---------------------------|--|--|--|--|------|--|--|--|--|-------|-------------------------|
| IEC EN 60598-1 RG 0 | | | | | IK03 | | | | | 650°C | T _a 0 +35 |
|---------------------------|--|--|--|--|------|--|--|--|--|-------|-------------------------|

Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire. LED driver, with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Class II electrical (this product is not earthed), IP40_IP20, Impact strength: IK03. Body: steel sheet, finished white (close to RAL9016). Diffuser: UV-stabilised polycarbonate hexagonal comfort optic. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 597 x 597 x 55 mm
 Luminaire input power: 28.2 W
 Luminaire luminous flux: 3800 lm
 Luminaire efficacy: 135 lm/W
 Weight: 5.57 kg



TLG_OMP2_F_QMPT_PDB.jpg



TLG_OMP2_M_Q.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Omega Pro 2

92916282 OP2 3800-840 HX HF E3D Q600

THORN