

# Beta 3

# THORN

## 96634491 BETA 3 4100-840 HF E3 LRO Q600

IEC EN 60598-1 RG 0		 ↓IP20 ↑IP44	IK03				650°C	T <sub>a</sub> 0 +25
---------------------------	--	--------------------	------	--	--	--	-------	-------------------------


### Beta 3

A square ceiling recessed LED luminaire. Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44\_IP20, Impact strength: IK03. Body: steel sheet, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Supplied with safety wire. Complete with 4000K LED.

Dimensions: 596 x 596 x 34 mm  
Luminaire input power: 33.6 W  
Luminaire luminous flux: 4100 lm  
Luminaire efficacy: 122 lm/W  
Weight: 3.6 kg



TLG\_BET3\_F\_MREQ.jpg



TLG\_BET3\_M\_Q600.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting