

## R2L2

96268461 R2L2 S 36L35 740 EWS CL1 GY

THORN

|          |      |      |   |   |   |   |                           |
|----------|------|------|---|---|---|---|---------------------------|
| ISO 9223 | IP66 | IK08 |  |  |  |  | T <sub>a</sub> -25<br>+50 |
| C5       |      |      |   |   |   |   |                           |

### R2L2

A small size LED road lighting lantern with 36 LEDs driven at 350mA with Extra Wide Street optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Complete with 4000K LED.

Dimensions: 655 x 362 x 155 mm

Luminaire input power: 40 W

Luminaire luminous flux: 6001 lm

Luminaire efficacy: 150 lm/W

Weight: 9.51 kg

Scx: 0.05 m<sup>2</sup>



TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**R2L2**

**96268461 R2L2 S 36L35 740 EWS CL1 GY**

THORN