

96262126 LINN RCT LED 6L50 832 + 96262133 LINN RCT FR GL FRAME + 96264336 LINN RCT BOLLARD EXTENSION

IP65	IK10			850 °C	T _a 35	
------	------	---	---	--------	-------------------	--

Linn

A rectangular, Recessed LED luminaire for pathway lighting applications. Electronic, fixed output control gear. Class I electrical, IP65, IK10. Body: die-cast aluminium, painted dark grey (Akzo Nobel 900). Glass: tempered glass, 8mm thick. Recessed housing (required, to be ordered separately): polypropylene. Complete with 3200K LED

Dimensions: 102 x 229 x 92 mm

Weight: 0.67 kg

Equipped with:
Frosted glass frame for rectangular Linn luminaire.


Equipped with:
Bollard mounting accessory for Linn rectangular luminaires.
Body: die-cast aluminium, powder coated dark grey.

Dimensions: 239 x 92 x 550 mm

Weight: 4.35 kg



TLG_LINN_F_RECTPDB.jpg



TLG_LINN_M_LDBOLCOMF.wmf

Linn

THORN

96262126 LINN RCT LED 6L50 832

+ 96262133 LINN RCT FR GL FRAME

+ 96264336 LINN RCT BOLLARD EXTENSION