

# Arena Symphony

THORN

96645132 ARENA LED6500-840 HF E3 TW WL6 EFL

IP20	IK03					650°C	T <sub>a</sub> 0 +25	
------	------	---	---	---	---	-------	-------------------------	--

## Arena Symphony

A suspended architectural raft, incorporating a direct/indirect LED luminaire. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP20. Raft and luminaire frame: aluminium. Optic: flat acrylic. Supplied with a 6 pole Wieland plug on 3.4m of 6 core cable and a panel mounted 6 pole Wieland socket for through wiring. Supplied with suspension wires. Complete with 4000K LED.

Dimensions: 2200 x 850 x 100 mm

Luminaire input power: 54.9 W


Luminaire luminous flux: 6300 lm

Luminaire efficacy: 115 lm/W

Weight: 24.6 kg



TLG\_ARNS\_F\_EFL.jpg



TLG\_ARNS\_M\_LD1.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

# Arena Symphony

96645132 ARENA LED6500-840 HF E3 TW WL6 EFL

THORN