

Arena Symphony

THORN

96645143 ARENA LED5000-840 HFIX E3 TW WL6 EDP

| | | | | | | | |
|------|------|---|----|---|---|-------|-------------------------|
| IP20 | IK03 | ⊕ | CE |  |  | 650°C | T _a 0 +25 |
|------|------|---|----|---|---|-------|-------------------------|

Arena Symphony

A suspended architectural raft, incorporating a direct/indirect LED luminaire. Electronic, DALI dimmable control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP20. Raft and luminaire frame: aluminium. Optic: curved acrylic. Supplied with a 6 pole Wieland plug on 3.4m of 6 core cable and a panel mounted 6 pole Wieland socket for through wiring. Supplied with suspension wires. Complete with 4000K LED.

Dimensions: 2200 x 850 x 135 mm

Luminaire input power: 42 W

Luminaire luminous flux: 5200 lm

Luminaire efficacy: 124 lm/W

Weight: 23.2 kg



TLG_ARNS_F_EDP.jpg



TLG_ARNS_M_LD2.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Arena Symphony

96645143 ARENA LED5000-840 HFIX E3 TW WL6 EDP

THORN