

EyeKon LED

96628459 EYE VS LED1000-830 HF L ANT

THORN

| | | | | | | | | |
|-------------|------|------|---|---|---|---|-------|---------------------------|
| EN 55015 | IP65 | IK10 |  |  |  |  | 850°C | T _a -20 +35 |
|-------------|------|------|---|---|---|---|-------|---------------------------|


EyeKon LED

Round, impact resistant LED bulkhead luminaire.
Electronic, fixed output control gear. Class I electrical, IP65, IK10. Body: large size, die-cast aluminium (LM6), powder coated anthracite. Diffuser: opal polycarbonate with die-cast aluminium visor feature. Electrical connection via 3 x 2 x 2.5mm² terminal block. Complete with 3000K LED


Dimensions: Ø340 x 155 mm

Luminaire input power: 16 W

Weight: 3.5 kg



TLG_EYKN_F_LGVSANTHOP.jpg



TLG_EYKN_M_LGE.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

EyeKon LED

96628459 EYE VS LED1000-830 HF L ANT

THORN