

# IQ Wave

# THORN

## 92900247 IQ WAVE LED4100-830 HFSX Q597 MRE




### IQ Wave

Recessed modular, direct LED luminaire. Electronic, DALI dimmable control gear. Class I electrical, IP44\_IP20, IK03. Body: highly reflective steel. Frame and end caps: polycarbonate. Diffuser: polycarbonate with aluminium heatsink. Gear tray: powder coated white steel. Suitable for lay in or pull up (with accessory) installation. Integral mini-sensa head for full presence, daylight and remote control. Complete with 3000K LED

Dimensions: 597 x 597 x 97 mm  
Luminaire input power: 40 W  
Luminaire luminous flux: 4050 lm  
Luminaire efficacy: 101 lm/W  
Weight: 3.9 kg



TLG\_IQWV\_F\_PDBCEILING.jpg



TLG\_IQWV\_M\_600.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting