

92900337 IQ WAVE LED3100-830 HF E3 Q597 MRE

| | | | | | | | | |
|------------------|------|---|----|---|---|-------|-------------------------|--|
| ↓ IP20 ↑ IP44 | IK03 | ⊕ | CE | ⚡ | ☀ | 650°C | T _a 0 +25 | |
|------------------|------|---|----|---|---|-------|-------------------------|--|


IQ Wave

Recessed modular, direct LED luminaire. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44 IP20, IK03. Body: highly reflective steel. Frame and end caps: polycarbonate. Diffuser: polycarbonate with aluminium heatsink. Gear tray: powder coated white steel. Suitable for lay in or pull up (with accessory) installation. Complete with 3000K LED

Dimensions: 597 x 597 x 97 mm
 Luminaire input power: 30 W
 Luminaire luminous flux: 3050 lm
 Luminaire efficacy: 102 lm/W
 Weight: 4.4 kg



TLG_IQWV_F_PDBCEILING.jpg



TLG_IQWV_M_600.wmf

This product contains a light source of energy efficiency class D.

IQ Wave

92900337 IQ WAVE LED3100-830 HF E3 Q597 MRE

THORN