

# Piazza II LED

THORN

96666259 PIAZZA II LED 1690-840 HF P ANT

IP65	IK10					T <sub>a</sub> -20 +40
------	------	---	---	---	---	---------------------------

## Piazza II LED

A robust Wall mounted luminaire. Electronic, fixed output control gear. Back plate: die-cast aluminium, painted anthracite. Body: anthracite polycarbonate. Ø20mm cable entry via rear or side conduit entries, BESA compatible. IP65, IK10. Complete with 4000K LED. Equipped with Mini Photocell.

Dimensions: 381 x 196 x 305 mm

Luminaire input power: 15.4 W


Luminaire luminous flux: 1844 lm

Luminaire efficacy: 120 lm/W

Weight: 2.8 kg



TLG\_PIA2\_F\_PDB.jpg



TLG\_PIA2\_M\_LD1.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting