

Piazza II LED

9666260 PIAZZA II LED 1690-840 HFI-X EC ANT

IP65	IK10						T _a -20 +40
------	------	--	--	--	--	--	---------------------------


Piazza II LED

A robust Wall mounted luminaire. Electronic, DALI dimmable control gear suitable for central battery emergency installations. Back plate: die-cast aluminium, painted anthracite. Body: anthracite polycarbonate. Ø20mm cable entry via rear or side conduit entries, BESA compatible. IP65, IK10. Complete with 4000K LED.

Dimensions: 381 x 196 x 305 mm
 Luminaire input power: 15.4 W
 Luminaire luminous flux: 1844 lm
 Luminaire efficacy: 120 lm/W
 Weight: 2.8 kg



TLG_PIA2_F_PDB.jpg



TLG_PIA2_M_LD1.wmf

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Piazza II LED

96666260 PIAZZA II LED 1690-840 HFI-X EC ANT

THORN