

## Prisma

96630827 PRISMA LED3000-840 HF FR L600 TW

EN 55015	IP44		IK06					650°C
-------------	------	--	------	--	--	--	--	-------

### Prisma

Slim Surface mounted LED luminaire. Electronic, fixed output control gear. Class I electrical, IP44. Body: pre-coated steel. End caps: white plastic. Diffuser: frosted acrylic. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 500mm. Two cable entries Ø19mm in the rear of the body and knockouts in the endcaps. Grommets included. Electrical connection via 3 x 2 x 2.5mm<sup>2</sup> piano key terminal block. Through Wiring. Complete with 4000K LED

Dimensions: 616 x 166 x 64 mm  
 Luminaire input power: 27 W  
 Luminaire luminous flux: 3100 lm  
 Luminaire efficacy: 115 lm/W  
 Weight: 1.52 kg



TLG\_PRSM\_F\_01.jpg



TLG\_PRSM\_M\_LED\_LD1.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

**Prisma**

**96630827 PRISMA LED3000-840 HF FR L600 TW**

**THORN**