

Prisma

96630840 PRISMA LED4400-840 HFIX FR L1200 TW

EN 55015	IP44		IK06				650°C
-------------	------	--	------	--	--	--	-------

Prisma

Slim Surface mounted LED luminaire. Electronic, DALI dimmable control gear. Class I electrical, IP44. Body: pre-coated steel. End caps: white plastic. Diffuser: frosted acrylic. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 1100mm. Two cable entries Ø19mm in the rear of the body and knockouts in the endcaps. Grommets included. Electrical connection via 5 x 2 x 2.5mm² piano key terminal block. Through Wiring. Complete with 4000K LED

Dimensions: 1216 x 166 x 64 mm
 Luminaire input power: 35.3 W
 Luminaire luminous flux: 4250 lm
 Luminaire efficacy: 120 lm/W
 Weight: 2.81 kg



TLG_PRSM_F_01.jpg



TLG_PRSM_M_LED_LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Prisma

96630840 PRISMA LED4400-840 HFIX FR L1200 TW

THORN