


# Voyager Star

THORN

96631652 VOYAGER STAR MSC SPOT ECC WH




## Voyager Star

High performance, surface mounted LED emergency lighting luminaire, with spot lighting optic.. Housing: aluminium die casting alloy, powder coated white (close to RAL9016). Gear tray: galvanised steel sheet. Lens: polycarbonate. IP40,. Luminaire can be installed quickly and maintained without tools. Electrical connection (230VAC) via maximum 2.5mm<sup>2</sup> cable, loop in - loop out possible. Optimum thermal management via heat sink. Complete with LEDs..

Luminaire input power: 3 W  
Dimensions: 146 x 146 x 34 mm  
Weight: 1 kg



TLG\_VSTR\_F\_MSC\_side\_ECx\_SPOT\_WH.jpg



TLG\_VYLD\_M\_MCE SPOT.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting