

		IK03					650°C		T _a -20 +25
---	---	------	---	---	---	---	-------	---	---------------------------

IQ Wave


Recessed modular, direct LED luminaire. Electronic, dimmable control gear, Wireless controlled via App with Bluetooth® 4.x - basicDIM Wireless, (installation in metal ceilings not allowed). Luminaire arrangement: Mobile control to luminaire max. 15 m, luminaire to luminaire max. 4 m (centre). Class I electrical, IP44_IP20, IK03. Body: highly reflective steel. Frame and end caps: polycarbonate. Diffuser: polycarbonate with aluminium heatsink. Gear tray: powder coated white steel. Suitable for lay in or pull up (with accessory) installation. Complete with 3000K LED

Radio definition: basicDIM Wireless - Bluetooth® 4.x,
Radio frequency: 2.4...2.483 GHz, Radio power: +4 dBm.

Dimensions: 597 x 597 x 97 mm
Luminaire input power: 30 W
Luminaire luminous flux: 3050 lm
Luminaire efficacy: 102 lm/W
Weight: 3.8 kg



TLG_IQWV_F_PDBCEILING.jpg



TLG_IQWV_M_600.wmf

This product contains a light source of energy efficiency class D.

IQ Wave

92910604 IQ WAVE LED3100-830 BC Q597 MRE

THORN