

## Omega Pro 2

92913445 OP2 3000-840 MPT HF E3 Q600

IEC EN 60598-1 RG 0			 ↓ IP20 ↑ IP40	IK03					650°C	T <sub>a</sub> 0 +35
---------------------------	--	--	----------------------	------	--	--	--	--	-------	-------------------------

### Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire. LED driver, with 3 hour, manual test, emergency lighting circuit. Class II electrical (this product is not earthed), IP40\_IP20, Impact strength: IK03. Body: steel sheet, finished white (close to RAL9016). Diffuser: UV-stabilised polycarbonate microprismatic optic for maximised spacing. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 597 x 597 x 55 mm  
 Luminaire input power: 24.4 W  
 Luminaire luminous flux: 3000 lm  
 Luminaire efficacy: 123 lm/W  
 Weight: 5.56 kg



TLG\_OMP2\_F\_QMPT\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.