

# Omega Pro 2

92913448 OP2 3000-840 MPT HFIX E3D Q600

THORN

|                           |   |   |      |   |   |   |   |       |                         |  |
|---------------------------|---|---|------|---|---|---|---|-------|-------------------------|--|
| IEC EN<br>60598-1<br>RG 0 |  |  | IK03 |  |  |  |  | 650°C | T <sub>a</sub> 0<br>+35 |  |
|---------------------------|---|---|------|---|---|---|---|-------|-------------------------|--|

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, DALI-2 dimmable with 3 hour, Self/DALI  
Addressable test, emergency lighting circuit. Class II  
electrical (this product is not earthed), IP40\_IP20, Impact  
strength: IK03. Body: steel sheet, finished white (close to  
RAL9016). Diffuser: UV-stabilised polycarbonate  
microprismatic optic for maximised spacing. Electrical  
connection via piano key terminals, loop-in/loop-out  
possible. Complete with 4000K LED, Colour Rendering  
Index min.: 80

Dimensions: 597 x 597 x 55 mm  
Luminaire input power: 23.7 W  
Luminaire luminous flux: 3000 lm  
Luminaire efficacy: 127 lm/W  
Weight: 5.57 kg



TLG\_OMP2\_F\_QMPT\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## **Omega Pro 2**

**92913448 OP2 3000-840 MPT HFIX E3D Q600**

THORN