

Omega Pro 2

92913457 OP2 3000-840 OP HFIX Q600


THORN

IEC EN 60598-1 RG 0			IK03					650 °C	
---------------------------	---	---	------	---	---	---	---	--------	--

Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.
LED driver, DALI-2 dimmable. Class II electrical (this product is not earthed), IP44_IP20, Impact strength: IK03.
Body: steel sheet, finished white (close to RAL9016).
Diffuser: UV-stabilised polymethylmethacrylate opal optic for wide light distribution. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 597 x 597 x 55 mm
Luminaire input power: 23.7 W
Luminaire luminous flux: 2850 lm
Luminaire efficacy: 120 lm/W
Weight: 5.05 kg



TLG_OMP2_F_QO_PDB.jpg



TLG_OMP2_M_Q.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Omega Pro 2

92913457 OP2 3000-840 OP HFIX Q600

THORN