

# Omega Pro 2

92914499 OP2 4400-830 CKIT HX BC Q600

THORN

IEC EN 60598-1 RG 0			IK03					650°C	T <sub>a</sub> 0 +35	
---------------------------	---	---	------	---	---	---	---	-------	-------------------------	--

## Omega Pro 2


A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, Wireless controlled via App with Bluetooth® 4.  
x - basicDIM Wireless. Class II electrical (this product is not  
earthed), IP40\_IP20, Impact strength: IK03. Body: steel  
sheet, finished white (close to RAL9016). Diffuser: UV-  
stabilised polycarbonate hexagonal comfort optic.  
Electrical connection via 7 pole piano key terminals, loop-  
in/loop-out possible. Complete with 3000K LED, Colour  
Rendering Index min.: 80

Radio definition: basicDIM Wireless - Bluetooth® 4.x,  
Radio frequency: 2.4...2.483 GHz, Radio power: +4 dBm.

Dimensions: 597 x 597 x 57 mm  
Luminaire input power: 32.9 W  
Luminaire luminous flux: 4150 lm  
Luminaire efficacy: 126 lm/W  
Weight: 5.44 kg



TLG\_OMP2\_F\_QH\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## Omega Pro 2

92914499 OP2 4400-830 CKIT HX BC Q600

THORN