

# Omega Pro 2

92916290 OP2 4400-840 CKIT+ MPT PIR Q600

THORN

IEC EN 60598-1 RG 0			IK03					650°C	T <sub>a</sub> 0 +35	
---------------------------	---	---	------	---	---	---	---	-------	-------------------------	--

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, DALI-2 dimmable. Class II electrical (this product is not earthed), IP40\_IP20, Impact strength: IK03.  
Body: steel sheet, finished white (close to RAL9016).  
Diffuser: UV-stabilised polycarbonate microprismatic optic for maximised spacing with central control pod hole.  
Equipped with presence detector and daylight harvesting function for dimming control via DALI. Electrical connection via 7 pole piano key terminals, loop-in/loop-out possible.  
Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 597 x 597 x 57 mm  
Luminaire input power: 35 W  
Luminaire luminous flux: 4450 lm  
Luminaire efficacy: 127 lm/W  
Weight: 5.43 kg



TLG\_OMP2\_F\_QMPTKIT\_PDB.jpg



TLG\_OMP2\_M\_QKIT.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## **Omega Pro 2**

**92916290 OP2 4400-840 CKIT+ MPT PIR Q600**

THORN