
Omega Pro 2



92916314 OP2 3800-840 HX HF E3D 3X12




Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire. LED driver, with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Class II electrical (this product is not earthed), IP40_IP20, Impact strength: IK03. Body: steel sheet, finished white (close to RAL9016). Diffuser: UVstabilised polycarbonate hexagonal comfort optic. Electrical connection via piano key terminals, loop-in/loopout possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm Luminaire input power: 28.2 W Luminaire luminous flux: 3800 lm Luminaire efficacy: 135 lm/W

Weight: 5.8 kg





TLG_OMP2_M_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Omega Pro 2 92916314 OP2 3800-840 HX HF E3D 3X12

