








Omega Pro 2

92916315 OP2 3800-840 HX HFIX E3D 3X12

THORN

IEC EN 60598-1 RG 0				IK03					650°C	T _a 0 +35	
---------------------------	---	---	---	------	---	---	---	---	-------	-------------------------	--


Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.
LED driver, DALI-2 dimmable with 3 hour, Self/DALI
Addressable test, emergency lighting circuit. Class II
electrical (this product is not earthed), IP40_IP20, Impact
strength: IK03. Body: steel sheet, finished white (close to
RAL9016). Diffuser: UV-stabilised polycarbonate hexagonal
comfort optic. Electrical connection via piano key
terminals, loop-in/loop-out possible. Complete with 4000K
LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm
Luminaire input power: 27.4 W
Luminaire luminous flux: 3800 lm
Luminaire efficacy: 139 lm/W
Weight: 5.8 kg



TLG_OMP2_F_RH_PDB.jpg



TLG_OMP2_M_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting