

# Omega Pro 2

# THORN

92916325 OP2 4400-840 MPT HFIX E3 3X12

|                           |  |  |  |  |      |  |  |  |  |       |                         |
|---------------------------|--|--|--|--|------|--|--|--|--|-------|-------------------------|
| IEC EN<br>60598-1<br>RG 0 |  |  |  |  | IK03 |  |  |  |  | 650°C | T <sub>a</sub> 0<br>+35 |
|---------------------------|--|--|--|--|------|--|--|--|--|-------|-------------------------|

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire. LED driver, DALI-2 dimmable with 3 hour, manual test, emergency lighting circuit. Class II electrical (this product is not earthed), IP40\_IP20, Impact strength: IK03. Body: steel sheet, finished white (close to RAL9016). Diffuser: UV-stabilised polycarbonate microprismatic optic for maximised spacing. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm  
Luminaire input power: 35 W  
Luminaire luminous flux: 4450 lm  
Luminaire efficacy: 127 lm/W  
Weight: 5.79 kg



TLG\_OMP2\_F\_RMPT\_PDB.jpg



TLG\_OMP2\_M\_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

# Omega Pro 2

92916325 OP2 4400-840 MPT HFIX E3 3X12

THORN