

# Omega Pro 2

92916338 OP2 3000-840 OP HFIX E3D 3X12

THORN

IEC EN 60598-1 RG 0		IK03			650°C
---------------------------	--	------	--	--	-------

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, DALI-2 dimmable with 3 hour, Self/DALI  
Addressable test, emergency lighting circuit. Class II  
electrical (this product is not earthed), IP44\_IP20, Impact  
strength: IK03. Body: steel sheet, finished white (close to  
RAL9016). Diffuser: UV-stabilised polycarbonate opal optic  
for wide light distribution. Electrical connection via piano  
key terminals, loop-in/loop-out possible. Complete with  
4000K LED, Colour Rendering Index min.: 80

Dimensions: 1197 x 297 x 57 mm  
Luminaire input power: 23.7 W  
Luminaire luminous flux: 2850 lm  
Luminaire efficacy: 120 lm/W  
Weight: 5.8 kg



TLG\_OMP2\_F\_RH\_PDB.jpg



TLG\_OMP2\_M\_L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## **Omega Pro 2**

**92916338 OP2 3000-840 OP HFIX E3D 3X12**

THORN