

ISO 9223 C3	ida DARK SKY APPROVED		IP66	IK09		CE			T _a 35	
----------------	--------------------------	--	------	------	--	----	--	--	-------------------	--

Urba Deco


A smart, sophisticated architectural urban lantern with 48 LEDs driven at 500mA and a Wide Street Comfort (symmetrical) optic with no upward light. Electronic, fixed output control gear. Class I electrical, IP66, Impact strength: IK09. Canopy and base: die-cast aluminium (AS9U3, LM24 equivalent, EN AC-46000) textured black (close to RAL9005). Enclosure: 6mm thick clear glass. Pre-wired with 1m cable. Suspended through 34G, luminaire perpendicular to the road. Complete with 3000K LED.

Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 510 x 241 x 146 mm
 Luminaire input power: 69.8 W
 Luminaire luminous flux: 10642 lm
 Luminaire efficacy: 152 lm/W
 Weight: 6.53 kg
 Scx: 0.031 m²



TLG_URBD_F_MSUPDB.jpg



TLG_URBD_M_MUS.wmf

Urba Deco

96279228 UD 48L50-730 WSC-S CL1 WS1 MSU-T BK U0

THORN