

## Omega Pro 2

92919333 OP2 3000-840 CKIT HX Q600

|                           |  |  |  |  |      |  |  |  |  |       |                         |
|---------------------------|--|--|--|--|------|--|--|--|--|-------|-------------------------|
| IEC EN<br>60598-1<br>RG 0 |  |  |  |  | IK03 |  |  |  |  | 650°C | T <sub>a</sub> 0<br>+35 |
|---------------------------|--|--|--|--|------|--|--|--|--|-------|-------------------------|

### Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire. LED driver, DALI-2 dimmable. Class II electrical (this product is not earthed), IP40\_IP20, Impact strength: IK03. Body: steel sheet, finished white (close to RAL9016). Diffuser: UV-stabilised polycarbonate hexagonal comfort optic. Electrical connection via 7 pole piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 80

Dimensions: 597 x 597 x 55 mm  
 Luminaire input power: 22.3 W  
 Luminaire luminous flux: 3000 lm  
 Luminaire efficacy: 135 lm/W  
 Weight: 5.4 kg



TLG\_OMP2\_F\_QH\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class D.