

**96633691 CONT3 4L50-830 NB NG IN ANT**

ISO 9223  
C5  IP 66 IK 08    T<sub>a</sub> - 20  
+ 35


## Contrast

A small architectural Bracket mounted LED floodlight with LEDs driven at 500mA and a narrow beam distribution. ., Pre-wired with IP66 connector, gear box to be ordered separately. Class II electrical (this product is not earthed), IP66, IK08. Body: die-cast aluminium (EN AC-44300), powder coated, textured anthracite (close to RAL7043). Compatible with coastal environments. Glass: tempered, 5mm thick. Gasket: EPDM. Screws: geomet. Complete with 3000K LED

Dimensions: Ø83 x 103 mm  
Luminaire input power: 8 W  
Luminaire luminous flux: 466 lm  
Luminaire efficacy: 58 lm/W  
Weight: 0.89 kg



TLG\_CON3\_F\_XS.jpg



TLG CONL M 4L.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting