

Omega Pro 2

92920012 OP2 3000-840 CKIT MPT BC 3X12

THORN

IEC EN 60598-1 RG 0				IK03					650°C	T _a 0 +35	
---------------------------	--	--	--	------	--	--	--	--	-------	-------------------------	--

Omega Pro 2


A recessed/surface/suspended, edge-lit LED luminaire.
LED driver, Wireless controlled via App with Bluetooth® 4.
x - basicDIM Wireless. Class II electrical (this product is not
earthed), IP40_IP20, Impact strength: IK03. Body: steel
sheet, finished white (close to RAL9016). Diffuser: UV-
stabilised polycarbonate microprismatic optic for maximised
spacing. Electrical connection via 7 pole piano key
terminals, loop-in/loop-out possible. Complete with 4000K
LED, Colour Rendering Index min.: 80

Radio definition: basicDIM Wireless - Bluetooth® 4.x,
Radio frequency: 2.4...2.483 GHz, Radio power: +4 dBm.

Dimensions: 1197 x 297 x 57 mm
Luminaire input power: 23.7 W
Luminaire luminous flux: 3000 lm
Luminaire efficacy: 127 lm/W
Weight: 5.67 kg



TLG_OMP2_F_RMPT_PDB.jpg



TLG_OMP2_M_L.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting