

92925247 POPPACK LED 6000 840 PIR E3 L1500

IP20	IK03					650°C	T _a 0 +25	
------	------	---	---	---	---	-------	-------------------------	--


PopPack

Batten LED luminaire with detachable LED engine.
Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic.
Electrical connection via 2 x ((3 + 5) x 2 x 2.5mm²) terminal blocks. Including pre-wired PIR sensor with switch ON/OFF functionality. Enabled control of slave luminaire from one master luminaire equipped with PIR sensor by means of hard wiring. 3 core wiring sufficient for the through wiring of the products, max. load per circuit = 2A. Complete with 4000K LED.

Dimensions: 1449 x 60 x 74 mm
Luminaire input power: 52.8 W
Luminaire luminous flux: 6400 lm
Luminaire efficacy: 121 lm/W
Weight: 1.65 kg



TLG_POPL_F_PDB_SENS.jpg



TLG_POPL_M_LD1.wmf

This product contains light sources of energy efficiency class D.

PopPack

92925247 POPPACK LED 6000 840 PIR E3 L1500

THORN