

## 92925252 POPPACK LED 9000 840 PIR E3 L1500

IP20	IK03					650°C	T <sub>a</sub> 0 +25	
------	------	---	---	---	---	-------	-------------------------	--


### PopPack

Batten LED luminaire with detachable LED engine.  
Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic.  
Electrical connection via 2 x ((3 + 5) x 2 x 2.5mm<sup>2</sup>) terminal blocks. Including pre-wired PIR sensor with switch ON/OFF functionality. Enabled control of slave luminaire from one master luminaire equipped with PIR sensor by means of hard wiring. 3 core wiring sufficient for the through wiring of the products, max. load per circuit = 2A. Complete with 4000K LED.

Dimensions: 1449 x 60 x 74 mm  
Luminaire input power: 63.6 W  
Luminaire luminous flux: 9100 lm  
Luminaire efficacy: 143 lm/W  
Weight: 1.67 kg



TLG\_POPL\_F\_PDB\_SENS.jpg



TLG\_POPL\_M\_LD1.wmf

This product contains light sources of energy efficiency class D.

**PopPack**

**92925252 POPPACK LED 9000 840 PIR E3 L1500**

**THORN**