

Omega Pro 2 Mini

96634430 OP2 900-940 OP HF E3 Q300 MRP

THORN

IEC EN 60598-1 RG 0	↓ IP20 ↑ IP40	IK03	⏏	CE	⚡	⊗	850°C	T _a 0 +35	
---------------------------	------------------	------	---	----	---	---	-------	-------------------------	--

Omega Pro 2 Mini


A shallow, versatile edge lit LED luminaire for lay-in and plasterboard ceilings as well as surface mounting with additional collar. LED driver, Fixed output with 3 hour, manual test, emergency lighting circuit. Class II electrical (this product is not earthed), IP20, Impact strength: IK03. Body: steel sheet, finished white (close to RAL9016). Diffuser: UV-stabilised polymethylmethacrylate opal optic for wide light distribution. Electrical connection via piano key terminals, loop-in/loop-out possible. Complete with 4000K LED, Colour Rendering Index min.: 90

..

Dimensions: 297 x 297 x 46 mm
Luminaire input power: 10.5 W
Luminaire luminous flux: 855 lm
Luminaire efficacy: 81 lm/W
Weight: 1.64 kg



TLG_OMP2_F_Q3OP.jpg



TLG_OMP2_M_Q3.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting