

Beta 3

THORN

96634498 BETA 3 4100-830 HF LRO Q600

| | | | | | | | | | | | |
|---------------------------|------------------|------|--|----|--|--|--|--|--------|---------------------------|--|
| IEC EN 60598-1 RG 0 | ↓ IP20 ↑ IP44 | IK03 | | CE | | | | | 650 °C | T _a -20 +40 | |
|---------------------------|------------------|------|--|----|--|--|--|--|--------|---------------------------|--|

Beta 3

A square ceiling recessed LED luminaire. Fixed output LED driver. Class II electrical (this product is not earthed), IP44_IP20, Impact strength: IK03. Body: steel sheet, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Supplied with safety wire. Complete with 3000K LED.

Dimensions: 596 x 596 x 34 mm
Luminaire input power: 33.6 W
Luminaire luminous flux: 3690 lm
Luminaire efficacy: 110 lm/W
Weight: 2 kg



TLG_BET3_F_MREQ.jpg



TLG_BET3_M_Q600.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting