

## Beta 3


96634498 BETA 3 4100-830 HF LRO Q600

IEC EN 60598-1 RG 0	↓ IP20 ↑ IP44	IK03						650 °C	T <sub>a</sub> -20 +40
---------------------------	------------------	------	--	--	--	--	--	--------	---------------------------


### Beta 3

A square ceiling recessed LED luminaire. Fixed output LED driver. Class II electrical (this product is not earthed), IP44\_IP20, Impact strength: IK03. Body: steel sheet, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Supplied with safety wire. Complete with 3000K LED.

Dimensions: 596 x 596 x 34 mm  
 Luminaire input power: 33.6 W  
 Luminaire luminous flux: 3690 lm  
 Luminaire efficacy: 110 lm/W  
 Weight: 2 kg



TLG\_BET3\_F\_MREQ.jpg



TLG\_BET3\_M\_Q600.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
 © Thorn Lighting