

## Beta 3

THORN

### 96634511 BETA 3 4800-840 HF LRO 3X12

IEC EN 60598-1 RG 0	↓ IP20 ↑ IP44	IK03		CE					650 °C	T <sub>a</sub> -20 +40	
---------------------------	------------------	------	--	----	--	--	--	--	--------	---------------------------	--


#### Beta 3

A rectangular ceiling recessed LED luminaire. Fixed output LED driver. Class II electrical (this product is not earthed), IP44\_IP20, Impact strength: IK03. Body: steel sheet, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Supplied with safety wire. Complete with 4000K LED.

Dimensions: 1196 x 296 x 34 mm  
Luminaire input power: 39.2 W  
Luminaire luminous flux: 4800 lm  
Luminaire efficacy: 122 lm/W  
Weight: 2.4 kg



TLG\_BET3\_F\_MRER.jpg



TLG\_BET3\_M\_3X12.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**Beta 3**

**96634511 BETA 3 4800-840 HF LRO 3X12**

THORN