

Omega Pro 2

THORN

92916533 OP2 4400-840 CKIT+ MPT BC E3D Q600

+ ANT: open area emergency optic

IEC EN 60598-1 RG 0			IK03				650°C	T _a 0 +35	
---------------------------	--	--	------	--	--	--	-------	-------------------------	--


Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.
LED driver, Wireless controlled via App with Bluetooth® 4.
x - basicDIM Wireless with 3 hour, Self/DALI Addressable
test, emergency lighting circuit. Class II electrical (this
product is not earthed), IP40_IP20, Impact strength: IK03.
Body: steel sheet, finished white (close to RAL9016).
Diffuser: UV-stabilised polycarbonate microprismatic optic
for maximised spacing with central control pod hole.
Electrical connection via 7 pole piano key terminals, loop-
in/loop-out possible. Complete with 4000K LED, Colour
Rendering Index min.: 80


Radio definition: basicDIM Wireless - Bluetooth® 4.x,
Radio frequency: 2.4...2.483 GHz, Radio power: +4 dBm.

Dimensions: 597 x 597 x 57 mm
Luminaire input power: 35 W
Luminaire luminous flux: 4450 lm
Luminaire efficacy: 127 lm/W
Weight: 5.96 kg

Equipped with:
Optics polycarbonate lens for anti-panic emergency
lighting.



TLG_OMP2_F_QMPTKIT_PDB.jpg



TLG_OMP2_M_QKIT.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting