

IEC EN 60598-1 RG 1	UK CA			halogen	IK 06		CE		850°C	T <sub>a</sub> -20 +25	
---------------------------	----------	--	--	---------	-------	--	----	--	-------	---------------------------	--


## Cetus3

A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, DALI dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible. Loop in - loop out possible. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical (this product is not earthed), IP44\_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 4000K LED

Dimensions: Ø195 x 100 mm  
 Luminaire input power: 8.6 W  
 Luminaire luminous flux: 1057 lm  
 Luminaire efficacy: 123 lm/W  
 Weight: 0.68 kg



TLG\_CTU3\_F\_M\_LED\_RWH\_Persp.jpg



TLG\_CTU3\_M\_HFM.wmf

This product contains a light source of energy efficiency class C.

**Cetus3**

**92943485 CETUS3 M 1000-840 HFIX RWH**

THORN