


IEC EN 60598-1 RG 1	UK CA		IP20 ↑ IP43	halogen	IK03		CE			850°C	T _a 5 25	
---------------------------	----------	--	----------------	---------	------	--	----	--	--	-------	------------------------	--

Cetus3


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø190-230 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical (this product is not earthed), IP43_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 4000K LED

For installation in concrete ceilings please contact sales

Dimensions: Ø248 x 100 mm
 Luminaire input power: 17.9 W
 Luminaire luminous flux: 2208 lm
 Luminaire efficacy: 123 lm/W
 Weight: 0.93 kg



TLG_CTU3_F_L_LED_RWH_Persp.jpg



TLG_CTU3_M_HFL.wmf

This product contains a light source of energy efficiency class C.

Cetus3

92943777 CETUS3 L 2000-840 HF E3 RWH

THORN