

IEC EN 60598-1 RG 1	UK CA				halogen	IK03		CE				850°C	T _a 5 25	
---------------------------	----------	--	--	--	---------	------	--	----	--	--	--	-------	------------------------	--

Cetus3


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, DALI dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical (this product is not earthed), IP43_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 3000K LED

For installation in concrete ceilings please contact sales

Dimensions: Ø195 x 100 mm
 Luminaire input power: 26.9 W
 Luminaire luminous flux: 3089 lm
 Luminaire efficacy: 115 lm/W
 Weight: 1.21 kg



TLG_CTU3_F_M_LED_RWH_Persp.jpg



TLG_CTU3_M_HFM.wmf

This product contains a light source of energy efficiency class D.

Cetus3

92943850 CETUS3 M 3000-830 HFIX E3D RWH

THORN